

# DF560L HIGH-PERFORMANCE HYDRAULIC ROCK DRILL

Doofor DF560L is a high-frequency hydraulic rock drill specially designed for underground production drilling and tunneling. The DF560L has a very low overhead, only 84mm from the drill center line. The rotation motor of the DF560L can be installed on the right hand or the left hand side. The rock drill uses air or water flushing.



## TECHNICAL SPECIFICATIONS

### DOOFOR DF560L DRIFTER




NOMINAL PERCUSSION POWER		20 kW	26.8 hp
OPTIMAL MAXIMUM HOLE SIZE		89 mm	3 1/2"
PERCUSSION FLOW		110–130 l/min	29.1–34.3 gpm
PERCUSSION PRESSURE		80–150 bar	1160–2176 psi
ROTATION MOTOR MAXIMUM FLOW <sup>1)</sup>	80cc	80 l/min	21.1 gpm
	100cc	90 l/min	23.8 gpm
	125cc	90 l/min	23.8 gpm
	160cc	90 l/min	23.8 gpm
	200cc	90 l/min	23.8 gpm
ROTATION TORQUE <sup>1)</sup>	80cc	504 Nm	372 lb-ft
	100cc	634 Nm	468 lb-ft
	125cc	796 Nm	587 lb-ft
	160cc	975 Nm	719 lb-ft
	200cc	1170 Nm	863 lb-ft
ROTATION PRESSURE MAXIMUM		175 bar	2540 psi
ROTATION SPEED MAXIMUM	80cc	250 rpm	
	100cc	250 rpm	
	125cc	250 rpm	
	160cc	250 rpm	
	200cc	250 rpm	
LUBRICATION	Air-oil mist	200–300 g/h	7.8–11.7 fl oz/h (2.3–3.5 dl/h)
LUBRICATION PRESSURE		6–7 bar	87–101 psi
LUBRICATION AIR FLOW		200–300 l/min	53–79 gpm
FLUSHING AIR PRESSURE <sup>1)</sup>		5–7 bar	73–101 psi
FLUSHING AIR FLOW <sup>1)</sup>		4000 l/min	1057 gpm
FLUSHING WATER FLOW <sup>1)</sup>		50–150 l/min	13–40 gpm
FLUSHING TEMPERATURE		3–30°C	37–86°F
RECOMMENDED MAXIMUM FEED FORCE		15 kN	3372 lbf
MAXIMUM OPERATING OIL TEMPERATURE		70 °C	158 °F
WEIGHT		152 kg	335 lb
SHANK SIZE		R32, R38, T38, T45	

<sup>1)</sup> Intermittent value.

<sup>2)</sup> Actual values vary according to drilling conditions and equipment.



**DIMENSIONS**



Rotation motor can be turned in 90° steps. Motors with back ports are available.  
 Gear box can be turned 180 degrees.  
 Flushing head can be turned 180 degrees.

DF560L can be equipped with BLT, EXT- and 2M options.